

XT SERIES



SPECIFICATIONS	XT	XT UR	XT UR HD	XT PLUS/6x6 (REAR ONLY)
TYPE OF VEHICLE	ATV	UTV	UTV	ATV / UTV
RECOMMENDED MAX GVW	2,500 lbs	3,500 lbs	4,200 lbs	2,500 / 3,500 / 4,200 lbs
FRAME CONSTRUCTION	Aluminum			
SPROCKET DRIVE UPGRADE	Yes	Yes	Yes	Yes
ASSEMBLY WEIGHT	121 lbs	127 lbs	151 lbs	146 / 152 / 182 lbs
SUSPENSION	Adjustable			
SUSPENSION LINKS	2	4		2 or 4
SUSPENSION SPRINGS	Double	Triple	Quad	Double+, Triple+ or Quad+
TRACK TREAD WIDTH	11"			
TRACK TREAD STYLE	All-Terrain, Self-Cleaning			
RUBBER TRACK CONSTRUCTION	Rods, Std Ply, Std Cord	Rods, HD Ply, Std Cord	Rods, HD Ply, HD Cord	
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°			
GROUND CONTACT LENGTH	(Hard Surface) 27" / (Soft Surface) 39"			(Hard Surface) 43" / (Soft Surface) 53"
GROUND CONTACT SURFACE AREA	297 sq in min / 429 sq in max			473 sq in min / 583 sq in max
SPROCKET DIAMETER (STANDARD)	14"			
ROAD WHEEL COUNT	8, 2 rows			10, 2 rows
WHEEL MATERIAL	UMHW / Rubber			
PAINT COLOR	Natural Aluminum			

* ALL SPECS ARE PER CORNER

MODELS IN SERIES: XT, XT UR, XT UR HD - Plus and 6x6 available on each



YAMAHA GRIZZLY ON XT



POLARIS RZR XP 1000 ON XT UR



BOBCAT 3450 ON XT UR HD