

MATTRACKS SALES, INC

MATTRACKS
Model 150-M1-A1-SA-SD
HEAVY DUTY 4X4 VEHICLES

Easy Steering Extra Heavy Duty up to
12,500 lbs. or 5,670 kg GVW



SPECIFICATIONS


Exclusive Anti-Torque System	Rubber Torsion - Anti Torque
Frame Construction	Steel
Assembly Weight1,590 lbs. @ 420/375 lbs. ea. (720 kg @ 190/170 kg ea.)
	Ft. - 150-M1-A1 w/Steering Assist
	Rr. - 150-M1
Type of Vehicle***	Heavy Duty 4x4 Vehicles
Recommended Max. Gross Wt.****	12,500 lbs. (5,670 kg) GVW, 6,250 lbs. (2,835 kg) per axle
Internal Suspension	Ft. - Concentric Pivot w/ Independent Offset Rocker Arm (for easy steering)
	Rr. - Concentric Pivot - Rigid
Track Tread Width16 in. (406 mm)
Tread Style	All-Terrain Self-Cleaning
Track Material	Rubber with Internal Composite Rods/Cord
Recommended Operating Temperature	(Ambient) -38° F to +130° F (-40° C to +55° C)
Overall Width Increase from Standard*15 in. to 18 in. (380 mm to 460 mm)
Increase Ground Clearance*1-1/2 in. to 6 in. (40 mm to 150 mm)
	Mattracks Position Vehicle Over Axle Center @19.75 in. (500 mm)
Lowers Center of Gravity*1-1/2 in. to 2-1/2 in. (40 mm to 60 mm)
Ground Contact Length:	
(Hard Surface)41 in. min. (1,040 mm min.)
(Soft Surface)59 in. max. (1,500 mm max.)
Ground Contact Surface Area	2,624 sq. in. min. (16,900 sq. cm min.)
	3,776 sq. in. max. (24,360 sq. cm max.)
Ground Pressure1.4 to 2.8 psi (.01 to .02 Nmm ²)
Sprocket Diameter18.5 in. (470 mm)
Gear-Reduction1/3 Increase in Gear Reduction on
	Vehicle with 30 in. (760 mm) Standard Tire
Wheels (Double shielded & Sealed Bearing)Front 8"x 2" HD Extra Seals
	Rear 8"x 2 1/2" HD Extra Seals
	(10 Front, 12 Rear / corner, 2 rows)
Wheel MaterialUHMW and Rubber
Paint (color)Yellow-Standard
	Other Colors - "Optional"
	E Coat Corrosion
	Resistance - "Optional"

PERFORMANCE

Recommended Max. Speed**40 mph (64 km/h)
Turning RadiusSame as original vehicle
Approach Angle*Up to 90°
Departure Angle*Up to 80°
Grade Capacity*100%
Side Slope Capacity*68%
Terrain - All Terrain Including Hard Surface	@ 12,500 lbs. (5,670 kg) GVW
Maximum Distance Off RoadIndefinite
Maximum Distance Hard Surface**At Below 80° F (26° C): Indefinite
	.At Above 80° F (26° C): 15 Miles @ 40 mph
	(22 km @ 64 km/h)



TRACK-STEER ASSIST ACCESSORY KIT



*Depending on vehicle **For maximum tread life
***Some vehicles may require slight alterations.
****Do not exceed manufacturer's vehicle capacities.

ALL SPECIFICATIONS ARE APPROXIMATE, YOUR VEHICLE'S PERFORMANCE MAY DIFFER. WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

2-4-08 Copyright Mattracks Sales, Inc., Karlstad, MN