

MATTRACKS SALES, INC

MATTRACKS
Model 150-M1-A1-SA
HEAVY DUTY 4X4 VEHICLES

Heavy Duty Vehicles up to
12,500 lbs. or 5,670 kg GVW



TRACK-STEER ASSIST ACCESSORY KIT



SPECIFICATIONS

Exclusive Anti-Torque System	Rubber Torsion - Anti Torque
Frame Construction	Steel
Assembly Weight	1,630 lbs. @ 420/395 lbs. ea. (740 kg @ 190/180 kg ea.)
Type of Vehicle***	Heavy duty 4x4 vehicles
Recommended Max. Gross Wt.****	12,500 lbs. (5,670 kg) GVW, 6,250 lbs. (2,835 kg) per axle
Internal Suspension	Concentric Pivot w/ Independent Offset Rocker Arm (for extra smooth ride)
Track Tread Width	16 in. (406 mm)
Tread Style	All-Terrain Self-Cleaning Lug
Track Material	Rubber with Internal Composite Rods/Cord
Recommended Operating Temperature	(Ambient) -38°F to +130°F (-40°C to +55°C)
Overall Width Increase from Standard*	15 in. to 18 in. (380 mm to 508 mm)
Increase Ground Clearance*	1-1/2 in. to 6 in. (40 mm to 150 mm)
Mattracks Position Vehicle Over Axle Center @19.75 in. (500 mm)		
Lowers Center of Gravity*	1-1/2 in. to 2-1/2 in. (40 mm to 60 mm)
Ground Contact Length:		
(Hard Surface)41 in. min. (1,040 mm min.)
(Soft Surface)59 in. max. (1,500 mm max.)
Ground Contact Surface Area	2,624 sq. in. min. (16,900 sq. cm min.) 3,776 sq. in. max. (24,360 sq. cm max.)
Ground Pressure	1.4 to 2.8 psi (.01 to .02 Nmm ²)
Sprocket Diameter	18.5 in. (470 mm)
Gear-Reduction	1/3 increase in Gear Reduction on Vehicle with 30 in. (760 mm) Standard Tire
Wheels (Double shielded and sealed bearing)8 in. x 2 in. HD Extra Seals (10/corner, 2 rows)
Wheel Material	UHMW and Rubber
Paint (color)	Yellow-Standard Other colors - "Optional" E Coat Corrosion Resistance - "Optional"

PERFORMANCE

Recommended Max. Speed**40 mph (64 km/h)
Turning RadiusSame as original vehicle
Approach Angle*Up to 90°
Departure Angle*Up to 80°
Grade Capacity*100%
Side Slope Capacity*68%
Terrain - All Terrain Including Hard Surface	@ 12,500 lbs. (5,670 kg) GVW
Maximum Distance Off RoadIndefinite
Maximum Distance Hard Surface**At below 80°F (26°C): Indefinite At above 80°F (26°C): 15 miles @ 40 mph (22 km @ 64 km/h)

*Depending on vehicle **For maximum tread life
***Some vehicles may require slight alterations.
****Do not exceed manufacturer's vehicle capacities.

ALL SPECIFICATIONS ARE APPROXIMATE, YOUR VEHICLE'S PERFORMANCE MAY DIFFER. WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

2-4-08 Copyright Mattracks Sales, Inc., Karlstad, MN