

## XT UR HD

Heavy Duty design featuring reinforced suspension and idler wheels along with a versatile aggressive utility-rated tread, HD rated patented Four Link Shape Changing Suspension and rubber torsion anti-torque system



Exclusive Anti-Torque System	Rubber Torsion - Anti-Torque
Frame Construction	Aluminum Cast
Assembly Weight	604 lbs @ 151 ea (272 kg @ 68 ea)
Type of Vehicle	UTV
Recommended Gross Vehicle Weight	4,200 lbs (1,905 kg)
Internal Suspension	Adjustable 4-link, quad spring SCS
Track Tread Width	11 in (279 mm)
Tread Style	XT 1 in (25 mm) lugs
Track Material	Rubber w/ HD Internal Composite, Rods, HD Cord
Recommended Operating Temperature	(Ambient) -40°F to +130°F (-40°C to +55°C)
Increase Ground Clearance*	5.5 in (140 mm)
Ground Contact Length (approx)	(Hard Surface) - 27 in (686 mm) (Soft Surface) - 39 in (991 mm)
Ground Contact Surface Area (approx)	1,188 sq in min (7,664 sq cm min) 1,716 sq in max (11,071 sq cm max)
Sprocket Diameter	14 in (356 mm)
Gear-Reduction	1/3 Increase on Vehicle w/ Typical OEM Tire
Wheels	8 per corner, 2 rows
Wheel Material	Aluminum, UHMW & Rubber
Color	Natural Aluminum - Standard

\*DEPENDENT ON VEHICLE, CARGO, AND ACCESSORIES \*\*SOME VEHICLES MAY REQUIRE SLIGHT ALTERATIONS  
ALL SPECIFICATIONS ARE APPROXIMATE AND WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION