

For 4 Wheel Drive Straddle ATVs
 Only



SPECIFICATIONS

Exclusive Anti-Torque System	Rubber Torsion - Anti Torque
Assembly Weight	Approx. 452 lbs @ 113 ea. (205 kg @ 51 ea.)
Type of Vehicle***	4 Wheel Drive ATVs
Recommended Max Gross Wt.	1,800 lbs. (816 kg)
Track Tread Width	11 in. (279 mm)
Tread Style	1 in. (25 mm) lugs (All-Terrain Self-Cleaning, Extra Traction)
Track Material	Rubber with Internal Composite and Cord
Recommended Operating Temperature	(Ambient) -40° F to +130° F (-40° C to +55° C)
Increase Ground Clearance*	5.5 in. (140 mm)
Ground Contact Length (approx.):		
(Hard Surface)	14 in. (356 mm) Front, 18 in. (457 mm) Rear
(Soft Surface)	39 in. max. (991 mm)
Ground Contact Surface Area (approx.)	704 sq. in. min. (4542 sq. cm min.)
	1,716 sq. in. max. (11,071 sq. cm max.)
Ground Pressure*	Less than 3/4 psi (5.2 kPa) on some ATVs
Sprocket Diameter	13 7/8 in. (352 mm)
Gear-Reduction	1/3 Increase in Gear Reduction on Vehicle with
Typical OEM ATV Tire		
Wheels (Shielded & Sealed Bearing)	8 wheels per corner, 2 rows
Wheel Material	UHMW & Rubber
Color	Natural Aluminum - Standard
	Camouflage Colors - "Optional"

NOTE: Mattracks offers a running board fender protector, which acts as a fender and foot guard saver, to protect the track lugs, foot guard and inside fender from occasional track contact. The skid plate style running board will be required on most installations to protect the track and ATV fenders from damage.

*Depending on vehicle, cargo, and accessories.
 **For maximum tread life
 ***Some vehicles may require slight alterations.

ALL SPECIFICATIONS ARE APPROXIMATE AND WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

2009 Copyright Mattracks, Inc., Karlstad, MN